



UBS-5540HD

55" FHD Ultra Bright Window Facing Signage

- > Full HD, 4,000nits ultra bright display ensures superior visibility
- > Slim, space saving and light weight design
- > Flat back design, ideal for use as digital displays and static poster dual-purpose signage
- > High performance media player supports both Linux and Windows OS for maximum flexibility
- > Leasing options are available

Spec

System Information	
Processor	Intel® Celeron® Processor N6210 1.5M Cache, up to 2.60 GHz
System Memory	8GB DDR4
Storage	256GB SSD
OS Compatibility	Win10 / Win11 / Linux
Connectivity	
Wi-Fi	IEEE802.11 a/b/g/n/ac
Bluetooth	Bluetooth 5.3
Ethernet	1 x Gigabit Ethernet Port
USB	1 x USB 3.2 Gen 1
Display	
Screen Size	55" TFT LCD
Native Resolution	1920 x 1080
Contrast Ratio	1000 : 1
Viewing Angle (H x V)	178 x 178
Color Depth	16.7 Million Colors
Portrait / Landscape	Yes / Yes
Brightness	4000 nit
Dimming Control	Yes
Backlight MTBF	100,000 hours
Power Requirement	
Power Supply	350W Power Supply Input: 100~240Vac / 50~60Hz
Power Consumption	265W (Typ.)
Mechanical	
Dimension (W x L x H)	1333 x 715 x 65 mm
Weight	35 Kg (Approx.)
Mounting	Supports Ceiling Mount Supports VESA 400 mm x 400 mm

Environmental	
Operating Temp.	Direct Sunlight: 0°C to 30°C (32°F to 86°F) w/o Direct Sunlight: 0°C to 40°C (32°F to 104°F)
Storage Temp.	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	10% to 80%
Certification	
Certification	FCC Class B
Warranty	
Warranty	1 Year
Ordering Information	
UBS-5540HD	55" Full HD, 4000nits Ultra Bright LCD Signage with Built-In Celeron® N6210 Media Player

Outline drawing of standard module, (mm)

