



HBS-2310HD

23.8" FHD High Bright Window Facing Signage

- > Full HD, 1,000nits high bright display ensures superior visibility
- > Slim, space saving and light weight design
- > Flat back design, ideal for use as digital displays and static poster dual-purpose signage
- > High performance media player supports both Linux and Windows OS for maximum flexibility

+ Spec

System Information

Processor	Intel® Celeron® Processor J6412 1.5M Cache, up to 2.60 GHz
System Memory	8GB DDR4
Storage	256GB SSD
OS Compatibility	Win10 / Win11 / Linux

Connectivity

Wi-Fi	IEEE802.11 a/b/g/n/ac
Bluetooth	Bluetooth 5.3
Ethernet	1 x Gigabit Ethernet Port
USB	1 x USB 3.2 Gen 1

Display

Screen Size	23.8" TFT LCD
Native Resolution	1920 x 1080
Contrast Ratio	1000 : 1
Viewing Angle (H x V)	88 x 88
Color Depth	16.7 Million Colors
Portrait / Landscape	Yes / Yes
Brightness	1000 nit
Dimming Control	Yes
Backlight MTBF	50,000 hours

Power Requirement

Power Supply	120W AC Adapter Input: 100~240Vac / 50~60Hz Output: 24V @ 5A
Power Consumption	50W (Typ.)

Mechanical

Dimension (W x L x H)	320.4 x 564.2 x 43.6 mm
Weight	6.5 Kg (Approx.)
Mounting	Supports Ceiling Mount Supports VESA 100 mm x 100 mm

Environmental	
Operating Temp.	Direct Sunlight: 0°C to 30°C (32°F to 86°F) w/o Direct Sunlight: 0°C to 40°C (32°F to 104°F)
Storage Temp.	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	10% to 80%
Certification	
Certification	FCC Class B
Warranty	
Warranty	1 Year
Ordering Information	
HBS-2310HD	23.8" Full HD, 1000nits High Bright LCD Signage with Built-in Celeron® J6412 Media Player

Outline drawing of standard module, (mm)

